




PP-RCT SOLID WALL PIPE - PN16

CODE	OD	DN	s	d1	kg/m	SDR
D130-016	16	10	2.7	10.6	0.110	6
D125-020	20	15	2.3	15.4	0.139	9
D125-025	25	20	2.8	19.4	0.203	9
D125-032	32	25	2.9	26.2	0.284	11
D125-040	40	32	3.7	32.6	0.420	11
D125-050	50	40	4.6	40.8	0.640	11
D125-063	63	50	5.8	51.4	1.395	11
D125-075	75	-	6.8	61.4	1.440	11
D125-090	90	65	8.2	73.6	2.030	11
D125-110	110	80	10.0	90.0	3.080	11
D125-125	125	100	11.4	102.2	3.910	11
D125-160	160	125	14.6	130.8	6.330	11
D125-200	200	160	18.2	163.6	9.950	11
D125-250	250	200	22.7	204.6	15.289	11
D125-315	315	250	28.6	257.8	24.600	11
D125-400	400	-	36.3	327.4	39.560	11
D125-450	450	350	40.9	368.2	50.100	11
D125-500	500	400	45.4	409.2	61.700	11

DESCRIPTION

Material: PP-RCT
Type: Solid Wall
Pressure Rating: SDR6: PN 25
 SDR9: PN 20
 SDR11: PN 16
Identification: Green
Standard: DIN 8077 / 8078
Length: 4 Mtr
Application: Cold Water, Potable Water, Mechanical Systems, Cold Reticulation




PP-RCT 'CLIMATEC' FASER PIPE - PN16

CODE	OD	DN	s	d1	kg/m	SDR
D111-020	20	15	2.8	14.4	0.151	7.4
D111-025	25	20	3.5	18.0	0.232	7.4
D111-032	32	25	3.6	24.8	0.293	9
D111-040	40	32	3.7	32.6	0.439	11
D111-050	50	40	4.6	40.8	0.678	11
D111-063	63	50	5.8	51.4	0.996	11
D111-075	75	-	6.8	61.4	1.419	11
D111-090	90	65	8.2	73.6	2.039	11
D111-110	110	80	10.0	90.0	3.031	11
D111-125	125	100	11.4	102.2	3.760	11

DESCRIPTION

Material: PP-RCT
 Type: Solid Wall
 Pressure Rating: SDR7.4: PN 25
 SDR9: PN20
 SDR11: PN16
 Identification: Green with 4 grey stripes,
 1 orange stripe
 Standard: DIN 8077 / 8078
 Length: 4 Mtr
 Application: Potable Water, Hot and Cold
 Water Services, Mechanical
 services, Hot and Cold




PP-RCT 'CLIMATEC' LARGE BORE PIPE - PN10

CODE	OD	DN	s	d1	kg/m	SDR
D117-160	160	150	9.5	141.0	4.635	17
D117-200	200	180	11.9	176.2	7.321	17
D117-250	250	220	14.8	220.4	11.065	17
D117-315	315	250	18.7	277.6	17.229	17
D117-355	355	300	21.2	312.6	21.890	17
D117-400	400	350	23.7	352.6	27.808	17
D117-450	450	400	26.7	396.6	38.200	17
D117-500	500	450	29.7	440.6	45.000	17

DESCRIPTION


Material: PP-RCT
 Type: PP-RCT with Faser Composite
 Pressure Rating: PN 10
 Identification: Green with 4 grey stripes,
 1 orange stripe
 Standard: DIN 8077 / 8078
 Length: 4 Mtr
 Application: Potable Water, Hot and Cold
 Water Services, Mechanical
 services, Hot and Cold



PP-RCT 'WATERTEC' FASER PIPE - PN20

CODE	OD	DN	s	d1	kg/m	SDR
D101-020	20	15	2.8	14.4	0.151	7.4
D101-025	25	20	3.5	18.0	0.232	7.4
D101-032	32	25	3.6	24.8	0.340	9
D101-040	40	32	4.5	31.0	0.513	9
D101-050	50	40	5.6	38.4	0.746	9
D101-063	63	50	7.1	48.8	1.244	9
D101-075	75	-	8.4	58.2	1.700	9
D101-090	90	65	10.1	69.8	2.450	9
D101-110	110	80	12.3	85.4	3.647	9
D101-125	125	100	14.0	97.0	4.480	9


DESCRIPTION
Material: PP-RCT
Type: PP-RCT with Faser Composite
Pressure Rating: SDR7.4: PN 25
 SDR9: PN 20
Identification: Green with 4 grey stripes
Standard: DIN 8077 / 8078
Length: 4 Mtr
Application: High Pressure Potable Water and Cold Water Services
 High Pressure Hot Water
 High Pressure Mechanical services, Hot and Cold



PP-RCT 'WATERTEC' LARGE BORE FASER PIPE - PN16

CODE	OD	DN	s	d1	kg/m	SDR
D105-160	160	125	14.6	130.8	6.755	11
D105-200	200	160	18.2	163.6	10.640	11
D105-250	250	200	22.7	204.6	16.160	11
D105-315	315	250	28.6	257.8	25.387	11
D105-355	355	300	32.2	290.6	36.520	11
D105-400	400	-	36.3	327.4	40.601	11
D105-450	450	350	40.9	368.2	57.310	11
D105-500	500	400	45.4	409.2	-	11

DESCRIPTION
Material: PP-RCT
Type: PP-RCT with Faser Composite
Pressure Rating: PN 16
Identification: Green with 4 grey stripes
Standard: DIN 8077 / 8078
Length: 4 Mtr
Application: Potable Water
 Hot and Cold Water Services
 Mechanical services, Hot and Cold, Clean Compressed Air




PP-RCT LILAC FASER PIPE - PN16

CODE	OD	DN	s	d1	kg/m	SDR
D127-020	20	15	2.3	15.4	0.139	9
D127-025	25	20	2.8	19.4	0.203	9
D127-032	32	25	2.9	26.2	0.284	11
D127-040	40	32	3.7	32.6	0.420	11
D127-050	50	40	4.6	40.8	0.640	11
D127-063	63	50	5.8	51.4	1.395	11
D127-075	75	-	6.8	61.4	1.440	11
D127-090	90	65	8.2	73.6	2.030	11
D127-110	110	80	10.0	90.0	3.080	11

DESCRIPTION

Material:	PP-RCT
Type:	Solid Wall
Pressure Rating:	SDR9: PN 20 SDR11: PN 16
Identification:	Lilac Coloured
Standard:	DIN 8077 / 8078
Length:	4 Mtr
Application:	Recycled Water Systems



PP-RCT BLACK UV FASER PIPE - PN16

CODE	OD	DN	s	d1	kg/m	SDR
D101-020UV	20	15	2.8	14.4	0.151	7.4
D101-025UV	25	20	3.5	18	0.232	7.4
D101-032UV	32	25	3.6	24.8	0.293	9
D101-040UV	40	32	3.7	32.6	0.439	11
D101-050UV	50	40	4.6	40.8	0.678	11
D101-063UV	63	50	5.8	51.4	0.996	11
D101-075UV	75	-	6.8	61.4	1.419	11
D101-090UV	90	65	8.2	73.6	2.039	11
D101-110UV	110	80	10	90	3.031	11
D101-125UV	125	100	11.4	102.2	3.76	11

DESCRIPTION

Material:	PP-RCT
Type:	PP-RCT with Faser Composite
Pressure Rating:	SDR7.4: PN 25 SDR9: PN 20 SDR11: PN 16
Identification:	Black coloured
Standard:	DIN 8077 / 8078
Length:	4 Mtr
Application:	Potable Water Hot and Cold Water Services Mechanical services, Hot and Cold

