




MUSTANG 160

32MM-160MM



Ultimate Solutions.
Intelligent Delivery.



COMMENTS

This HDPE Drainage electrofusion machine is suitable for welding electrofusion fittings in HDPE from 32 to 160mm for non pressure drainage systems (will suit all brands including Coes, Vulcathene-Eurofusion, Akatherm, Geberit, Valsir, Waviduo).

MUSTANG 160 V2 automatically detects connection to the fitting to be welded and compensates current supplied according to ambient temperature. It is also capable of detecting any malfunction that could occur before or during welding procedures. MUSTANG 160 V2 is made in compliance with the current safety standards, and the is very lightweight which makes it extremely easy to carry around including a belt clip.

STANDARD COMPOSITION

- Welding machine complete with welding cable with 90 ° connectors
- fixing carabiner
- plastic carrying case
- manual scraper

TECHNICAL FEATURES

MODEL	MUSTANG 160
Working range	32 - 160 mm
Materials	HDPE
Power supply	230 V Single phase 50/60 Hz 10 Amp plug
Max. absorbed power	1000 W
Max. output current	5 A
Outside temperature range	-10° C - 45° C
Ambient temperature probe	Electronic
Protection degree	IP 54
Weight machine body (without accessories)	1 Kg
Weight with carrying case	3.45 Kg
Dimensions machine body	65 x 185 x 46 mm
Dimensions carrying case	400 x 330 x 160 mm