



Slim Flange - AS4087 Flange

PN16 RATED

STAINLESS STEEL
SDR11 (PN16) WITH AS4087 B7 TABLE D BACKING RING

CODE (STAINLESS FLANGE)	PE END SIZE	FLANGE SIZE	PRESSURE RATING	PIPE END SDR	PIPE ID FLANGE END (B)	FLANGE PCD	BOLT HOLES NO. X DIA.	FLANGE COMBINED THICKNESS (C)
3463-2521	250mm	200mm (8")	PN16	SDR11	183mm	292mm	8×18	51
3463-3125	315mm	250mm (10")	PN16	SDR11	228mm	356mm	8×22	57
3463-3530	355mm	300mm (12")	PN16	SDR11	256mm	406mm	12×22	63
3463-4030	400mm	300mm (12")	PN16	SDR11	256mm	406mm	12×22	63
3463-4035	400mm	350mm (14")	PN16	SDR11	289mm	470mm	12×26	70
3463-4037	400mm	375mm (15")	PN16	SDR11	325mm	495mm	12×26	75
3463-4537	450mm	375mm (15")	PN16	SDR11	325mm	495mm	12×26	75
3463-4540	450mm	400mm (16")	PN16	SDR11	325mm	521mm	12×26	75
3463-5045	500mm	450mm (18")	PN16	SDR11	366mm	584mm	12×26	90
3463-5650	560mm	500mm (20")	PN16	SDR11	407mm	641mm	16×26	98



Comments:

Check that both pipe(s) and fitting to be joined are compatible, only compatible materials should be joined together. Check the PN and SDR rating marked on fitting and compare with that of the pipe. If in doubt, seek advice from the manufacturer. Correct installation procedures should be followed.

The designs, materials and specifications shown are subject to change without notice. This is due to the continuous development of our product range

Contact our technical team for further information.